

MORSØ - H

Miter Machine

Semi-automatic, pneumatic Dust free operation **▼** Dust free operation

■ Exact 45° degree cut

Noise level below 70dB

MORSØ-H works after the same principle as the MORSØ-F, but pneumatically. MORSØ-H is activated through a safe dual hand release system in order to protect the operator from touching the knives during the work.

The MORSØ-H saves you from using your leg all the time to activate the machine, as the air cylinder that pulls the knives through the work piece secures an easy and effortless working procedure. The lever system is identical to the MORSØ-F. MORSØ-H is ideal for repetitive work and the noise level is only 70db.

As with all other MORSØ miter machines, there is no problem with dust as all the waste will be lead to the ground via the waste chute.

MORSØ-H leaves the cut surface of the wood perfectly smooth and accurate, requiring no further preparation before joining.

The special lever system of the machine ensures a very easy operation. The sliding longitudinal stop and measuring scale ensure accurate repetitive work.

MORSØ-EH TURBO is CE approved.





MORSØ - H

Miter Machine

Semi-automatic, pneumatic Dust free operation

TECHNICAL DATA

SUBJECT	SPECIFICATION
Double miter	45°
Single miter up to	90°
Cutting width maximum	100 mm (4")
Cutting height maximum	145 mm (5.7")
Square cutting	65/65 mm (2½")
Measuring scale up to	1,500 mm (60")
Air pressure	6-8 bar
Air Consumption per stroke	15 litres / 3.9 gal.
House Connector	10 mm (0.39")
Net weight	90 kilos (198 lbs)

MORSØ-H is delivered with:

- Safety guard
- · dual hand release operation
- waste chute
- sliding longitudinal stop
- measuring scale up to 1500 mm / 60"
- adjustable fences (45-90°)
- adjustable rabbet supports

ACCESSORIES:

- automatic rabbet supports
- manually operated digital measuring system up to 6,000 mm/240"
- deeper rabbet supports up to 70 mm 2¾"
- left hand extension table
- roller infeed tables
- · extra cast iron extension table and supporting leg
- flip stop
- wooden blade box for Morso blades
- vertical and/or horizontal moulding clamps





DIS	ΙK	IRO	IC	H